



Technical Specification

PhotoFluor® (CT-3675)

- Width: 14.0 cm (5.5 inches)
- Height: 21.6 cm (8.5 inches)
- Depth: 36.8 cm (14.5 inches)
- Weight: 5.45 kg (12lbs.)
- Operating mode: continuous
- Water protection: IPX0
- Main cable: 10 A/250 V
- Jack: IEC 320/C13
- Power supply: 100-240 V, 50/60 Hz, 3.15A
- Fuse: T3.15A 250V
- Cleaning: Surface cleaning with mild detergent

Liquid Light Guide

- Weight: 0.23 kg (0.5 lbs.)
- Length: 2.0 M (4.9 feet)
- Cleaning: Surface cleaning with mild detergent;
Optical components with Isopropyl alcohol

Lamp

- Type: 200 W Ushio EmArc SMR200 D1
- Output: Approx. 20 W with 5 mm core, 12 W with 3 mm core

Ambient conditions for operation

- Temperature: 10° to 25°C (50° to 77°F)
- Rel. humidity: 30% to 75%
- Air pressure: 700 hPa to 1060 hPa

Ambient conditions for storage (in shipping packaging)

- Temperature: 0° to +50°C (32° to 122°F)
- Rel. humidity: 0% to 100%, non-condensing

